

设计项目	191 说明书	图号	AP-191-PR-01
尺寸(mm)	195*140mm, 折后尺寸 97.5*140 mm	版本	V1.0
材质工艺	70g 书纸 正反两面印刷, 正面为英文, 反面为中文。	设计师	Tina
		日期	20180826
备注	料号: 519100040000		


140mm

Thank you for purchasing **Aputure** Barn Doors.


The Aputure F10 Barn Doors is a light-control product that works with Bowens Mount products such as the 600d Pro/600d/600x Pro/600x series. You can use eight light baffles to adjust the beam you want while blocking out the light that you don't want to get out. Eight-blade light-retaining blade design makes light control more flexible and diverse.

Application Scenarios


1. Pair with Adapter ring



2. Pair with Fresnel mount




Warning: Dont turn on the light when four leaves are folded!
Lamp light illuminate for a long time on the blade will make the blade very hot, beware of scald!






Installation

1. Install the adaptor ring on the lamp holder, and rotate the "movable claw" of the adaptor ring to the upper part during installation.




2. Lift the "movable claw" on the adaptor ring and rotate it to the back, put Barn Doors into the slot of the claw, then lift the claw and adjust it to the front and close it.




Safety rope installation

1. A small hook on the safetyrope hooks onto the F10 Fresnel hook ring.



2. Attach the big hook of the safety rope to the fixed buckle



*The F10 Fresnel is connected to the fastener by a safety rope, mainly to prevent accidental fall of the light baffle.

This product manual can be found on the Lighting page on www.aputure.com.

97.5mm


140mm

感谢您购买 **Aputure** 爱图仕八叶挡光板。


爱图仕10英寸八叶挡光板是一款与带保荣卡口的600d Pro/600d/600x Pro/600x等系列产品搭配使用的控光产品, 可以通过八片挡光板来调整你想要的光束, 同时挡住不想外漏的光。八叶挡光叶片设计, 控光更加灵活多样。

使用场景


1. 搭配自带转换件



2. 搭配菲涅尔



不能在叶片完全折合时开灯!
灯光长时间照射在叶片上会使叶片发烫, 谨防烫伤!






安装

1. 将转换环安装在灯头, 安装时将转换环“可活动卡爪”调至上方。




2. 将转换环上“可活动卡爪”提起旋转调到后方, 把Barn Doors放入卡爪卡槽内, 再提起卡爪调到前方关上即可。




安全绳安装

1. 安全绳小挂钩钩住 F10 Fresnel 上挂钩环



2. 安全绳大挂钩挂在固定扣位



*通过安全绳把挡光板与固定件连接, 主要是防止挡光板意外掉落

您可以在本公司网站cn.aputure.com中的炫彩视频系列栏目下找到此操作指南。

97.5mm